



BASİT. SEZGİSEL. MICROSOFT TEAMS ENTEĞRE

CCX 400, MICROSOFT TEAMS EDITION


Bazen tek ihtiyacınız olan güvenilir bir masaüstü telefondur. Her zaman güvenebileceğiniz ortak alanlar için her zaman çalışan, her zaman kullanıma hazır bir telefon olan Poly CCX 400, kullanımı kolay giriş seviyesi bir ofis telefondur. Arayüzü alışık olduğunuz basit ve sezgisel Teams'dir. Kişiler ve toplantılar, yerel bir Microsoft Teams deneyimi olan renkli bir dokunmatik ekrana tek bir dokunuşla veya tanıdık arama tuşlarını gösteren bu telefonları konuşlandırmayı seçebilirsiniz.

Poly CCX 400'ün Microsoft Teams Cihaz Portalı'ndan kurulması ve yönetilmesi kolaydır. Masaüstlerine ve resepsiyon masalarında kullanılabilir. İsteğe bağlı bir duvara montaj braketi ile duvara da monte edilebilir. Kablolu ağ bağlantısı için ethernet kablosu yoksa, isteğe bağlı Wi-Fi USB adaptörü kablosuz ağ bağlantısı sağlayacaktır, Wi-Fi bağlantı seçeneğinde CCX 400'ü ayrıca opsiyonel olarak alınabilen güç adaptörü ile devreye alabilirsiniz.

- Poly HD Voice ile görüşmeler net ses kalitesi
- Özel ödüllü Poli Acoustic Fence teknolojisi ile açık ofis ortamındaki dikkat dağıtıcı arka plan gürültüleri ortadan kaldırın
- Telefon kurulumu, desteğinin sağlanması ve yönetim kolaylığı ile BT desteğine ihtiyaç gerekmez
- CCX 400'ü Microsoft Teams Ortak Alan Telefonu (CAP) lisansı ile basit bir tuş takımıyla (sesli posta olmadan) kurabilirsiniz
- CCX 400'ü Microsoft Teams deneyimi olan giriş seviyesi bir telefon olarak kullanabilirsiniz

- 5 inç büyüklüğünde çok noktalı dokunmatik LCD ekran
- Ortak alan telefonu (CAP) veya yerel Microsoft Teams deneyimi ile kullanın
- Her nüansı Poly HD Ses ve Poli Acoustic Clarity ile duyabilirsiniz
- Poli Acoustic Fence ile dikkat dağıtıcı arka plan gürültüsünü ortadan kaldırın
- Dünya standartlarında yankı iptali ile tam çift yönlü hoparlör (handsfree)
- Opsiyonel CCX 400 duvara montaj kiti ile duvara monte edilebilir

POLY CCX 400



SPECIFICATIONS

USER INTERFACE FEATURES

- Gesture-based, multitouch-capable capacitive touch screen
- 5-inch color LCD (720 x 1280 pixel)
- 9:16 aspect ratio
- Screen saver
- On-screen virtual keyboard
- Voicemail support
- Adjustable base height
- One USB type-A port (2.0 compliant) for media and storage applications
- Unicode UTF-8 character support
- Adjustable font size selection (regular, medium, large)
- Normal and dark mode
- Multilingual user interface including Chinese, Danish, Dutch, English (Canada/US/UK), French, German, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Slovenian, Spanish, and Swedish

AUDIO FEATURES

- Poly HD Voice technology delivers lifelike voice quality for each audio path; handset, hands-free speakerphone, and optional headset
- Poly Acoustic Clarity technology providing full-duplex conversations, acoustic echo cancellation and background noise suppression
- TIA-920 wideband audio, type 1 compliant (IEEE 1329 full duplex)
- Frequency response—150 Hz–7 kHz for handset, optional headset and handsfree speakerphone modes
- Codecs: G.711 (A-law and μ -law), G.729AB, G.722 (HD Voice), G.722.1 iLBC
- Individual volume settings with visual feedback for each audio path
- Voice activity detection
- Comfort noise generation

- DTMF tone generation (RFC 2833 and in-band)
- Low-delay audio packet transmission
- Adaptive jitter buffers
- Packet loss concealment
- OPUS support

HEADSET AND HANDSET COMPATIBILITY

- Dedicated RJ-9 headset port
- Hearing aid compatibility to ITU-T P.370 and TIA 504A standards
- Compliant with ADA Section 508 Subpart B 1194.23 (all)
- Hearing aid compatible (HAC) handset for magnetic coupling to hearing aids
- Compatible with commercially-available TTY adapter equipment
- USB headset support

NETWORK AND PROVISIONING

- SIP protocol support
- SDP
- IETF SIP (RFC 3261 and companion RFCs)
- Two-port gigabit Ethernet switch
- 10/100/1000Base-TX across LAN and PC ports
- Conforms to IEEE802.3-2005 (Clause 40) for Physical media attachment
- Conforms to IEEE802.3-2002 (Clause 28) for link partner auto-negotiation
- Manual or dynamic host configuration protocol (DHCP) network setup
- Time and date synchronization using SNTP
- FTP/TFTP/HTTP/HTTPS server-based central provisioning for mass deployments
- Provisioning and call server redundancy supported¹
- QoS Support—IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP

- VLAN—CDP, DHCP VLAN discovery, LLDP-MED for VLAN discovery
- Network address translation support for static configuration and “keep-alive”
- SIP signaling
- RTCP and RTP support
- Event logging
- Syslog
- Hardware diagnostics
- Status and statistics reporting
- IPv4 and IPv6
- TCP
- UDP
- DNS-SRV

SECURITY

- 802.1X authentication and EAPOL Media encryption via SRTP
- Transport layer security (TLS)
- Encrypted configuration files
- Digest authentication
- Password login
- Support for URL syntax with password for boot server address
- HTTPS secure provisioning
- Support for signed software executables

POWER

- Built-in auto sensing IEEE 802.3af Power over Ethernet (Class 3) 13 W (Max)
- External Universal AC/DC Adapter (optional) 5 VDC @ 3 A (15 W)
- ENERGY STAR® rated

REGULATORY APPROVALS²

- Australia RCM
- Brazil ANATEL
- Canada ICES and NRTLc
- EEA CE Mark
- Eurasian Customs Union EAC
- Indonesia SDPPI
- Japan VCCI
- Mexico NYCE
- NZ Telepermit
- Saudi Arabia CITC
- South Africa ICASA
- South Korea KC
- USA FCC and NRTL

SAFETY

- UL 62368-1
- CAN/CSA C22.2 No. 62368-1-14
- EN 62368-1
- IEC 60950-1 & IEC 62368-1
- AS/NZS 62368-1

EMC

- FCC Part 15 Class B
- ICES-003 Class B
- EN 55032 Class B
- EN 55024
- CISPR32 Class B
- VCCI Class B

OPERATING SYSTEM

- Android 9

OPERATING CONDITIONS

- Temperature: 0 to 40 °C (+32 to 104 °F)
- Relative humidity: 5% to 95%, noncondensing

STORAGE TEMPERATURE

- -40 to + 70 °C (-40 to + 160 °F)

POLY CCX 400 BUSINESS MEDIA PHONE COMES WITH:

- Console
- Handset with handset cord
- Network (LAN) cable–CAT-5E
- Desk Stand
- Setup Sheet

SIZE

- 18.1 cm x 21.5 cm x 5.0 cm WxHxD
- 7.1 in x 8.5 in x 2.0 in WxHxD

PART NUMBER

- 2200-49700-019 CCX 400 Business Media Phone. Microsoft Teams/SFB. PoE. Ships without power supply
- 2200-49703-001 CCX 400 wall mount kit

WEIGHT

- Unit weight: 1.043 kg (2.23 lbs)

MASTER CARTON QUANTITY

- Ten (10)

¹Planned localization

²Planned compliance

³Skype for Business support planned for a future software update



VODANET İLETİŞİM HİZMETLERİ LTD. ŞTİ.

Altayçeşme Mah. Çamlı Sok. No:16
Dap Royal Center Kat:8/32 Maltepe - İSTANBUL

Telefon: +90 216 340 76 40
www.vodanet.com.tr

Faks: +90 216 340 51 73

info@vodanet.com.tr