



## BASİT. SEZGİSEL. MICROSOFT TEAMS ENTEĞRE

- Poly HD Voice ile görüşmeler net ses kalitesi sağlar
- Özel ödüllü Poli Acoustic Fence teknolojisi ile açık ofis ortamındaki dikkat dağıtıcı arka plan gürültüleri ortadan kaldırır
- Telefon kurulumu, desteğinin sağlanması ve yönetim kolaylığı ile BT desteğine ihtiyaç gerekmez
- Kişiler ve toplantılara, yerel bir Microsoft Teams deneyimi ile renkli bir dokunmatik ekrana bir dokunuşla kolayca erişilebilir
- Geleneksel ahizeye ek olarak her çalışanın tarzına uyacak birden fazla kulaklık seçeneği mevcuttur

### **POLY CCX 600**

Microsoft Teams için masaüstü telefonlardaki yeni standartla tanışın. Poly CCX 600 Business Media Phone, çalışanların her aramada profesyonel görüneceklerinden emin hissediyor. Polycom Acoustic Fence teknolojisi, CCX serisi Teams masaüstü telefon deneyiminin en önemli bileşenini (ses netliği) önemli ölçüde artırarak iş konuşmalarını yabancı seslerden ve dikkat dağıtıcı şeylerden uzak tutar. Poly Acoustic Clarity teknolojisi, Poly'den beklediğiniz üstün kaliteli ses deneyimini sunmak için yeni nesil endüstri lideri tam çift yönlü, yankı iptali ve gürültü azaltmayı gelişmiş ses işleme ile birleştirir.

7 inç renkli LCD (1024 x 600 piksel) boyutlarında çok noktalı dokunmatik özellikli kapasitif ekranı sayesinde Poly CCX 600 IP telefonu kullanmak oldukça kolaydır. Kişilere, toplantılara ve sesli mesajlara basit dokunmatik erişim sağlandığından kullanıcılar tüm Teams özelliklerini hızlı ve kolay kullanırlar. 16:9 en boy oranı ile kullanıcı dostu menü görünümü (geçmiş çağrı listesi, adres defteri gibi) yoğun iş temposu içinde kullanımı hızlandırmaya yardımcı olmaktadır. Poly tarafından CCX serisi tüm telefonlarda bulunan ekran üzerindeki sanal klavye bir çok özelliği yada telefon ayarını gerçekleştirirken işinizi çok kolaylaştırır. CCX 600 masa telefonunu kullanmadığınız zamanlarda ekran koruyucu özelliğini devreye alabilirsiniz.

- Yerel Microsoft Teams deneyimi
- 7 inç çoklu dokunmatik LCD ekran
- Her nüansı Poly HD Ses ve Poli Acoustic Clarity ile duyur
- Poli Acoustic Fence ile rahatsız edici arka plan gürültüsünü ortadan kaldırır
- Dünya standartlarında yankı iptali ile tam çift yönlü hoparlör çalışması
- Yeni nesil özellikleri destekleyen güçlü yonga setleri
- Entegre Wi-Fi dongle ile her yere kolayca kurulabilir
- Her stile uygun kulaklık seçenekleri (Bluetooth, USB, RJ9)

# POLY CCX 600



(order headset separately)

## SPECIFICATIONS

### USER INTERFACE FEATURES

- Gesture-based, multitouch-capable touchscreen
- 7" color LCD (1024 x 600 pixel)
- 16:9 aspect ratio Screensaver
- On-screen virtual keyboard
- Voicemail support
- Adjustable base height
- One USB type-A port (2.0 compliant) for media and storage applications
- One USB Type-C port (2.0 compliant) for media and storage applications
- Integrated Bluetooth 4.2
- Integrated Wi-Fi
- Unicode UTF-8 character support
- Adjustable font size selection (regular, medium, large)
- Normal and dark mode
- Multilingual user interface including Chinese, Danish, Dutch, English (Canada/US/UK), French, German, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Slovenian, Spanish, and Swedish

### AUDIO FEATURES

- Poly HD Voice technology delivers lifelike voice quality for each audio path: handset, hands-free speakerphone, and optional headset
- Poly Acoustic Clarity technology providing full duplex conversations, acoustic echo cancellation, and background noise suppression
- TIA-920 wideband audio, type 1 compliant (IEEE 1329 full duplex)
- Frequency response—100 Hz–20 kHz for handset, optional headset, and handsfree speakerphone modes
- Codecs: G.711 (A-law and  $\mu$ -law), G.729AB, G.722 (HD Voice), G.722.1 iLBC
- Individual volume settings with visual feedback for each audio path

- Voice activity detection
- Comfort noise generation
- DTMF tone generation (RFC 2833 and in-band)
- Low-delay audio packet transmission
- Adaptive jitter buffers
- Packet loss concealment
- OPUS support

### HEADSET AND HANDSET COMPATIBILITY

- Dedicated RJ-9 headset port
- Hearing aid compatibility to ITU-T P.370 and TIA 504A standards
- Compliant with ADA Section 508 Subpart B 1194.23 (all)
- Hearing aid compatible (HAC) handset for magnetic coupling to hearing aids
- Compatible with commercially-available TTY adapter equipment
- USB headset support
- Bluetooth headset support

### NETWORK AND PROVISIONING


- SIP protocol support
- SDP
- IETF SIP (RFC 3261 and companion RFCs)
- Two-port gigabit Ethernet switch 10/100/1000 Base-TX across LAN and PC ports
- Wi-Fi network connectivity—2.4–2.4835 GHz (802.11b, 802.11g, 802.11n HT-20)–5.15–5.825 GHz (802.11a, 802.11n, HT-20, 802.11n HT-40)
- Conforms to IEEE802.3-2005 (Clause 40) for physical media attachment
- Conforms to IEEE802.3-2002 (Clause 28) for link partner auto-negotiation
- Manual or dynamic host configuration protocol (DHCP) network setup
- Time and date synchronization using SNTP

- FTP/TFTP/HTTP/HTTPS server-based central provisioning for mass deployments
- Provisioning and call server redundancy supported<sup>1</sup>
- QoS Support—IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP
- VLAN—CDP, DHCP VLAN discovery, LLDP-MED for VLAN discovery - Network address translation support for static configuration and "keep-alive"
- SIP signaling
- RTCP and RTP support
- Event logging
- Syslog
- Hardware diagnostics
- Status and statistics reporting
- IPv4 and IPv6
- TCP
- UDP
- DNS-SRV

### SECURITY

- 802.1X authentication and EAPOL
- Media encryption via SRTP
- Encrypted configuration files
- Digest authentication
- Password login
- Support for URL syntax with password for boot server address
- HTTPS secure provisioning
- Support for signed software executables
- Wi-Fi encryption: WEP, WPA-Personal, WPA2-Personal, WPA2-Enterprise with 802.1X (EAP-TLS, PEAP-MSCHAPv2)

# POLY CCX 600



## POWER

- Built-in auto sensing IEEE 802.3at Power over Ethernet (Class 4) 25 W (Max)
- External universal AC/DC adapter (optional), 48 VDC @ 0.52A (25 W)

## REGULATORY APPROVALS<sup>2</sup>

- Argentina ENACOM
- Australia RCM
- Brazil ANATEL
- Canada ICES and NRTL
- China CCC and SRRC
- EEA CE Mark
- Eurasian Customs Union EAC
- India WPC
- Indonesia SDPPI
- Israel MOC
- Japan MIC & VCCI
- Malaysia SIRIM
- Mexico IFETEL and NYCE
- NZ Telepermit
- Saudi Arabia CITC
- Singapore IMDA
- South Africa ICASA
- South Korea KC
- Taiwan NCC
- UAE TRA
- USA FCC and NRTL

## RADIO

- USA-FCC Part 15.247 & FCC Part 15.407
- Canada-RSS 247 Issue<sup>2</sup>
- EU-ETSI EN 300 328 & ETSI EN 301 893
- Japan-Article 2.1 Item 19-2 and 19-3
- Australia-AS/NZ4268

## SAFETY

- UL 62368-1
- CAN/CSA C22.2 No. 62368-1-14
- EN 62368-1
- IEC 60950-1 and IEC 62368-1
- AS/NZS 62368-1

## EMC

- FCC Part 15 Class B
- ICES-003 Class B
- EN 55032 Class B
- EN 55024
- EN 301 489-1 and EN 301 489-3 and EN 301 489-17
- CISPR32 Class B
- VCCI Class B

## OPERATING CONDITIONS

- Temperature: 0 to 40 °C (+32 to 104 °F)
- Relative humidity: 5% to 95%, noncondensing

## STORAGE TEMPERATURE

- -40 to +70 °C (-40 to +160 °F)

## POLY CCX 600 BUSINESS MEDIA PHONE COMES WITH

- Console
- Handset with handset cord (handset model only)
- Network (LAN) cable-CAT-5E
- Desk stand
- Setup sheet

## SIZE

- With handset: 26.3 cm x 21.7 cm x 6.0 cm WxHxD (10.4 in x 8.5 in x 2.4 in WxHxD)
- Without handset: 19.0 cm x 21.7 cm x 6.0 cm WxHxD (7.5 in x 8.5 in x 2.4 in WxHxD)

## PART NUMBER

- 2200-49780-019 CCX 600 Business Media Phone. Microsoft Teams/SFB. PoE. Ships without power supply.
- 2200-49770-019 CCX 600 Business Media Phone without handset. Microsoft Teams/SFB. PoE. Ships without power supply.
- 2200-49743-001 CCX 600 wall mount Kit

## WEIGHT

- CCX 600 with handset unit weight: 1.97 kg (4.34 lbs)
- CCX 600 without handset unit weight: 1.30 kg (2.87 lbs)

## MASTER CARTON QUANTITY

- Five (5)

## WARRANTY

- One (1) year

<sup>1</sup> Planned localization

<sup>2</sup> Planned compliance